

szel 2% szel 2% szel 6%

2% +0.00 2%

kiesort kamienny gr. 10 cm  
grunt rodzimy

beton asfaltowy AC11S gr 4 cm  
beton asfaltowy AC11W gr 4 cm  
kruszywo łamane 0/31.5 gr. 30 cm

kieska granitowa 8x10 gr. 8cm  
beton B15 gr.10cm  
stabilizacja gr. 20 cm

Technical drawing of a road cross-section showing a 10m wide asphalt road with a 2% cross-slope, a 0.03m high curb, and a 0.08m deep drainage ditch. The drawing includes dimensions for the road width, curb height, and ditch depth, as well as material specifications for the road layers.

Dimensions and Slopes:

- Top width: 13.0m (5.1m + 5.0m + 2.9m)
- Bottom width: 10.0m (5.1m + 4.9m)
- Left side slope: 1:1.5
- Right side slope: 1:1.5
- Top surface slope: 2%
- Curb height: 0.03m
- Ditch depth: 0.08m
- Ditch bottom slope: 0.036%

Material Specifications:

- niesort kamienny gr. 10 cm
- grunt rodzimy
- beton asfalcowy AC11S gr 4 cm
- beton asfalcowy AC11W gr 4 cm
- kruszywo łamane 0/31.5 gr. 30 cm

Technical drawing of a road cross-section. The road width is 3.50m. The slopes are 2% on both sides. The curb height is 0.03m. The ditch depth is 0.04m. The drawing includes a legend for materials:

- 10 cm kamień (stone)
- 4 cm beton asfaltowy AC11W (asphalt concrete)
- 30 cm kruszywo łamane Ø31,5 gr. (crushed stone)
- 8 cm kostka granitowa (granite cube)
- 10 cm beton B15 gr. (concrete)
- 20 cm stabilizacja gr. (stabilization)

TEMAT	Przebudowa drogi gminnej w Niedamirowie		
OBIEKT	Droga Gminna w Niedamirowie		
ADRES OBIEKTU	Niedamirow, dz.145, 67, 87		
INWESTOR	Gmina Lubawka pl Wolności 1 58-420 Lubawka		
	IMIE I NAZWISKO SPECJALNOŚĆ / NUMER UPRAWNIEŃ	DATA	PODPIS
PROJEKTANT	mgr inż. Włodzimierz Lewowski upr. nr 228/02/DUW	II 2014	
ASYSTENT	mgr inż. Grzegorz Lewowski upr. nr 263/DOS/13	II 2014	
TREŚĆ RYS.	rys. 4 - przekroje konstrukcyjne skala 1:50		
JEDNOSTKA PROJEKTOWA	PRZEDSIĘBIORSTWO ROBÓT INŻYNIERYJNYCH "TRAKT" Siedziba: 50 58-410 Marciszów		